



PRECISION, QUALITY, &
SUPERIOR WORKMANSHIP

AIRBOATS



7'6" Hull
LS2 Engine
CH3 Gear Reduction
3 Blade Carbon Fiber Propellar
30" Aluminum Grass Rake
3/8" Polymer Bottom and Sides



15' x 8'
496 8.1 GM Levitator
Stainless Steel Powdercoated Super Structure
Located in Florida

15' x 7'6"
0-540 Lycoming Engine
Stainless Steel Super Structure
Located in Florida



21' X 7'9" Standard Aluminum Hull – V Crimped Sides
496 CID/425 HP 8.1 Levitator Engine
CH 3 2.3:1 Belt Drive Counter Rotator Reduction
4-Blade Carbon Fiber, R-Series, RHR 82"
3-Blade Carbon Fiber, R-Series, LHR 80"
3/8" Black Polymer on Bottom, 1/4" Polymer sides
36" Aluminum Grass Rake w/Painted webbing
Side Nav Lights reinforced w/HID Lights
Superstructure – Stainless Steel w/ 4 SS KC Lights mounted
Large AFCO Radiator & Oil Cooler w/SS Braided Oil Lines, Bottom Mounted
5' Aluminum Foam Filled Rudders on 32" Centers
60 gal Fuel Tank w/Electric Sender
Custom Center Panel w/Hummingbird GPS
4 Person Piratecom Intercom System w/connection to Operator,
Assistant, Gunner position and one passenger
Single Side by Side Rear Operator w/Aluminum Box
Two removable Fourman Front Passenger seats that can mount perpendicular
To Operator Seating or Face Forward (all seats equipped with seat belts)
Entire Boat, Grass Rake and parts painted in NATO Green - Heavy Webbing inside hull

NEW Hull Design
14% more flat bottom
Rounded Nose to eliminate water spray & better turning abilities.
20% improved planing
15% better top end speed



Standard Hull Specifications:

- Aluminum Welded Hull.190 5086 Bottom, Transom, & Splash Plate
 - .125 5052 Sides, Bulkhead, & Bow Cap
 - 5 - 2" X 2" X 1/4" Aluminum T-Bars on 7' Hulls
 - 7 - 2" X 2" X 1/4" Aluminum T- Bars on 7' 6" & 8' Hulls
 - Storage Opening in Bulkhead

Approximate Hull Weights:

- 7' Wide Hull: 30 lbs. per foot
- 7'6" Wide Hull: 35 lbs. per foot
- 8' Side Hull: 37 lbs. per foot

Ultra-Lite Hull Specifications:

- Aluminum Welded Hull
 - .125 6061 T-6 Bottom
- .125 5052 Sides, Bulkhead, Bow Cap, Transom, & Splash Plate
 - 5 - 2" X 2" X 1/4" Aluminum T-Bars on 7' Hulls
 - 7 - 2" X 2" X 1/4" Aluminum T- Bars on 7' 6" & 8' Hulls
 - Storage Opening in Bulkhead

Approximate Hull Weights:

- 7' Wide Hull: 24 lbs. per foot
- 7'6" Wide Hull: 29 lbs. per foot
- 8' Side Hull: 34 lbs. per foot